



SC11 Dome IP Site Camera

Image Sensor	1/2.7" Progressive CMOS	Power Input	IEEE 802.3af PoE class 2
Resolution	Ships as 1080p @ 30fps (WDR off). Max 5MP @ 20fps (WDR on)	Power Consumption	Max 6.49 W (IR on) Max 3.6 W (IR off)
Lens Type	Fixed	Pan Range	350°
Focus	Fixed	Tilt Range	75°
Focal Length	f=3.6mm	Rotation Range	350°
Aperture	F2.0	Ingress Protection (Weather)	IP66 - dust tight with powerful water protection
Iris	Fixed	Impact Protection (Vandal)	IK10 - protected against 20 joules of impact
Field of View	76° (Horizontal) 59° (Vertical) 100° (Diagonal)	Safety Certifications	CE, FCC Class B, UL, LVD, VCCI, C-Tick
Shutter Time	1/5 to 1/32,000 seconds	Humidity	90%
Day/Night	Yes	Operating Temperature	Starting: ~10°C ~ 60°C (14°F ~ 140°F) Working: ~30°C ~ 60°C (-22°F ~ 140°F)
IR Illuminators	Built-in up to 30 meters	Warranty	5 years
LED Indicator	System power and status indicator	Included Accessories	Quick installation guide Alignment sticker Screwpack Cable gland Mounting kits
Connectors	RJ-45 cable connectors for PoE connection		
Dimensions	117.2 × 89.6 mm (4.61 × 3.53 in)		
Weight	540 g (19.05 oz)		
Storage	Requires Site Gateway for centralized storage and monitoring (SG sold separately)		