



SC11 Dome IP Site Camera

| | | | |
|-----------------|---|------------------------------|--|
| Image Sensor | 1/2.7" Progressive CMOS | Power Input | IEEE 802.3af PoE class 2 |
| Resolution | 2560×1920 (5MP), Wide Dynamic Range (WDR) | Power Consumption | Max 6.49 W (IR on) Max 3.6 W (IR off) |
| Lens Type | Fixed | Pan Range | 350° |
| Focus | Fixed | Tilt Range | 75° |
| Focal Length | f=3.6mm | Rotation Range | 350° |
| Aperture | F2.0 | Ingress Protection (Weather) | IP66 - dust tight with powerful water protection |
| Iris | Fixed | Impact Protection (Vandal) | IK10 - protected against 20 joules of impact |
| Field of View | 103° (Horizontal) 76° (Vertical) 134° (Diagonal) | Safety Certifications | CE, FCC Class B, UL, LVD, VCCI, C-Tick |
| Shutter Time | 1/5 to 1/32,000 seconds | Humidity | 90% |
| Day/Night | Yes | Operating Temperature | Starting: ~10°C ~ 60°C (14°F ~ 140°F) Working: ~30°C ~ 60°C (-22°F ~ 140°F) |
| IR Illuminators | Built-in up to 30 meters | Warranty | 5 years |
| LED Indicator | System power and status indicator | Included Accessories | Quick installation guide Alignment sticker Screwpack Cable gland Mounting kits |
| Connectors | RJ-45 cable connectors for PoE connection | | |
| Dimensions | 117.2 × 89.6 mm (4.61 × 3.53 in) | | |
| Weight | 540 g (19.05 oz) | | |
| Storage | Requires Site Gateway for centralized storage and monitoring (SG sold separately) | | |