



# SC21 Bullet IP Site Camera

Image Sensor	1/2.7" Progressive CMOS	Power Input	IEEE 802.3af PoE class 2
Resolution	2560×1920 (5MP), Wide Dynamic Range (WDR)	Power Consumption	Max 6.49 W (IR on) Max 3.6 W (IR off)
Lens Type	Fixed	Pan Range	350°
Focus	Fixed	Tilt Range	90°
Focal Length	f=3.6mm	Rotation Range	180°
Aperture	F2.0	Ingress Protection (Weather)	IP67 - dust tight with immersion up to 1 m
Iris	Fixed	Impact Protection (Vandal)	IK10 - protected against 20 joules of impact
Field of View	30° ~ 100° (Horizontal) 23° ~ 72° (Vertical) 38° ~ 135° (Diagonal)	Safety Certifications	CE, FCC Class B, UL, LVD, VCCI, C-Tick
Shutter Time	1/5 to 1/32,000 seconds	Humidity	90%
Day/Night	Yes	Operating Temperature	Starting: ~10°C ~ 60°C (14°F ~ 140°F) Working: ~30°C ~ 60°C (-22°F ~ 140°F)
IR Illuminators	Built-in up to 50 meters	Warranty	5 years
LED Indicator	System power and status indicator	Included Accessories	Quick installation guide
Connectors	RJ-45 cable connectors for PoE connection		Alignment sticker
Dimensions	118 × 118 × 294 mm (4.65 × 4.65 × 11.57 in)		Screwpack
Weight	1254 g (44.23 oz)		Cable gland
Storage	Requires Site Gateway for centralized storage and monitoring (SG sold separately)		Mounting kits